

PAVADINIMAS

wesnothd – Mûðio dėl **Wesnoth** daugelio þaidėjų þaidimo tinklo demonas

REZIUMĖ

wesnothd [**-dv**] [**-c kelias**] [**-p prievadas**] [**-t skaièius**] [**-T skaièius**]
wesnothd -V

APRAÐYMAS

Manages Battle for Wesnoth multiplayer games. See <http://www.wesnoth.org/wiki/ServerAdministration> on what commands the server accepts via the wesnoth client or the socket.

PARAMETRAI

-c kelias, **--config kelias**

tells wesnothd where to find the config file to use. See the section **SERVER CONFIG** below for the syntax. You can reload the config with sending SIGHUP to the server process.

-d, **--daemon**

paleidþia wesnothd kaip demonà.

-h, **--help**

pasako Jums, kà daro komandinės eilutės parametrai.

--log-lygis=domenas1,domenas2,...

sets the severity level of the log domains. **all** can be used to match any log domain. Available levels: **error**, **warning**, **info**, **debug**. By default the **error** level is used and the **info** level for the **server** domain.

-p prievadas, **--port prievadas**

susieja serverà su nurodytu prievadu. Jeigu prievadas nenurodytas, tai bus naudojamas **15000** prievadas.

-t skaièius, **--threads skaièius**

sets the maximum number of waiting worker threads for network I/O to n (default: 5, max: 30).

-T skaièius, **--max-threads skaièius**

sets the maximum number of worker threads that will be created. If set to 0 there will be no limit (default: 0).

-V, **--version**

parodo versijos numerà ir iðsijungia.

-v, **--verbose**

turns debug logging on.

SERVERIO KONFIGÛRACIJA

Bandra sintaksė yra:

[*elementas*]

raktas="vertė"

raktas=¥vertė,vertė,...´

[/*elementas*]

Globalūs raktai:

connections_allowed

Leidþiamø prisijungimø skaièius ið to paties IP. 0 reiðkia begalybė. (numatyta: 5)

disallow_names

Names/nicks that are not accepted by the server. '*' and '?' from wildcard patterns are supported. See **glob(7)** for more details. Default values (used if nothing is specified) are: ***admin*,*admln*,*server*,ai,ai?,computer,human,network,player**.

max_messages

Leidþiamø praneðimø skaièius esanèiø **messages_time_period**. (numatyta: 4)

messages_time_period

The time period (in seconds) message flooding is detected in. (default: 10 seconds)



motd Dienos praneðimas.

passwd

Slaptaþodis naudojamas gauti administratoriaus teises. Paparstai jis prasideda `¥admin ´`.

versions_accepted

A comma separated list of version strings to be accepted by the server. ‘*’ and ‘?’ from wild-card patterns are supported. (defaults to the corresponding wesnoth version)

Pavyzdys: **versions_accepted**="*" priima bet kokià versijà.

Globalûs elementai:

[redirect] Elementas, nurodantis serveriui kur peradresuoti tam tikras klientø versijas.

host Serverio, á kurá peradresuoti, adresas.

port Prievadas, prie kurio jungtis.

version

A comma separated list of versions to redirect. Behaves the same way as **versions_accepted** in regard to wildcard patterns.

[proxy] Elementas nurodantis serveriui elgtis kaip proksi ir persiøsti visus prisijungusius klientus á nurodytà serverà. Priima tuos paèius raktus kaip ir **[redirect]**.

AUTORIUS

Paraðë David White <davidnwhite AT verizon DOT net>. Redagavo Nils Kneuper <crazy-ivanovic AT gmx DOT net>, ott <ott AT gaon DOT net> ir Soliton <soliton DOT de AT gmail DOT com>. Ðà dokumentacijos puslapá ið pradþiø paraðë Cyril Bouthors <cyril AT bouthors DOT org>.

Aplankykite oficialø puslapá: <http://www.wesnoth.org/>

COPYRIGHT

Copyright © 2003–2007 David White <davidnwhite AT verizon DOT net>

Tai yra laisva programa; ði programa licencijuota Free Software Foundation (Laisvos programinës árangos fondo) paskelbta GPL 2 versija. Nëra JOKIOS garantijos; netgi PERKAMUMO ar TINKAMUMO KONKRETIEMS TIKSLAMS.

TAIP PAT ÐIÛRËKITE

wesnoth(6), **wesnoth_editor(6)**

