

NAME

po2debconf - a tool to generate debconf templates from PO files

SYNOPSIS**Usage****po2debconf** [-v] [-h] [--podir=*THX_MáXXC*] [--o *TáXXP_TIN*] [-e *CHUáXXI*] *cháXX***DESCRIPTION****Overview**

ChXXng trAXnh nA y AXáXXc máXXi táXp tin PO vA máXXt táXp tin *templates* riAXng láXX, vA táXXo máXXt táXp tin máXXu Debconf cháXXa máXXi báXXn dáXXch, tXXng táXX váXXi táXp tin AXáXXc táXXo báXXi *debconf-mergetemplate* (1) (táXX gAXi *debconf-utils*). MáXXc AXáXXnh lA cAXc táXp tin PO AXáXXc tAXm trong th-1AEX máXXc con *po* báXn dXáXXi váXX trA cAXa táXp tin cháXX.

AXáXX giAXp chuyáXXn tiáXXp mAX ngAXn ngáXX cho tiáXXng Na Uy Bokmål, mAX ngAXn ngáXX *no* vA *nb* AXáXXc xáX lAX AXáXXc biáXXt. AXAX cAX táXp tin *no.po* thAX nAX nAXn báXX thay tAXn thA nh *nb.po*. DAXng *nb.po* sáXX lA m cho cAXc báXXn dáXXch kiáXXu cáXX -no láXXn -nb AXáXXu sáXXn sA ng trong táXp tin máXXu.

Lines beginning with a number sign (#) are comments in templates files. They are useful to give hints to translators, and are discarded by **po2debconf**. Special comments have been introduced in po-debconf 1.0. They are in the form **#flag:directive**. The **#flag:partial** is the only directive interpreted by **po2debconf**. Normally when a field is composed of several paragraphs (like **__Choices** and **_Description**), it is translated if all paragraphs are translated. When a field contains **#flag:partial**, translated strings may be mixed with untranslated strings.

OPTIONS**Options****-h, --help**

HiáXXn tháXX báXXn tAXm táXXt cAXch sáX dáXXng, ráXXi thoAXt.

-v, --verbose

XáX lAX áXX cháXX AXáXX chi tiáXXt (xuáXXt nhiáXXu dáXX liáXXu diáXXn táXX tiáXXn trAXnh, háXXu Ach AXáXX gáXX láXXi).

--podir=*THX_Má*AXáXXt th-1AEX máXXc cháXXa cAXc táXp tin PO. MáXXc AXáXXnh lA tAXm cAXc táXp tin PO trong th-1AEX máXXc con *po* báXn dXáXXi váXX trA cáXXa táXp tin cháXX.**-o, --output=*Tá******XXP_TIN***

AXáXXt tAXn táXp tin xuáXXt (máXXc AXáXXnh lA thiáXXt báXX xuáXXt chuáXXn).

-e, --encoding=*CHUá****XXI***

Convert encoding. Argument can take 3 values: **utf8** (convert to UTF-8), **po** (do not change encoding) and **popular** (convert encoding of input files depending on their language; the **PODEBCONF_ENCODINGS** environment variable must point to a name of a file containing the encoding map).

TAXn táXp tin nh-1AEX váXy hAXnh nh-1AEX :

```
#
#   Number is comment sign
#
cs      ISO-8859-2
da      ISO-8859-1
de      ISO-8859-1
el      ISO-8859-7
```

v.v.

BáXXng mAX máXXc AXáXXnh táXXng lA **popular**: nAX AXAX AXáXXc chuyáXXn AXáXXi sang **utf8** káXX táXX po-debconf 0.9.0.

EXAMPLES

KáXX táXX debconf 1.2.0, AXáXXnh dáXXng cáXXa máXXu AXAX thay AXáXXi: báXXng mAX thuXXc váXX tAXn trAXáXXng, táXXc lA tAXn trAXáXXng lA *foo-ngAXn_ngáXX.báXXng_mÁX*. PhiAXn báXXn debconf cÁX gáXXp trAXáXXng nA y thAX báX qua, khAXng xuáXXt thAXng AXiáXXp: cháXX hiáXXn tháXX vAXn báXXn gáXXc.



If present, a *po/output* file can override defaults for encoding and output format. It contains a single line with two fields. The first field is the output format (currently valid values are 1 for fields in the form *foo-lang*, and 2 for *foo-lang.encoding*) and the second field is the encoding, e.g.

```
echo '2 utf8' > po/output
```

cho phAXp **po2debconf** chuyáXXn AXáXXi vAXn báXXn sang UTF-8.

BáXXng mAX AXÁXXc AXáXXt thA nh po hay utf8 thAX AXáXXnh dáXXng xuáXXt luAXn luAXn AXÁXXc AXáXXt thA nh 2, AXáXX mA phiAXn báXXn debconf cÁX sáXX khAXng tháX hAXn tháXX vAXn báXXn theo báXXng mAX sai.

XEM CẢ XNG

debconf-gettextize(1), *debconf-updatepo*(1), *po-debconf*(7).

TA~ X& Glá

Denis Barbier <barbier AT linuxfr DOT org>

