

Padre::Task::PPI::IntroduceTemporaryVariable(3pm) Perl Documentation Padre::Task::PPI::IntroduceTemporaryVariable(3pm)

NAME

Padre::Task::PPI::IntroduceTemporaryVariable – Introduces a temporary variable using PPI

SYNOPSIS

```
my $tempvarmaker = Padre::Task::PPI::IntroduceTemporaryVariable->new(
    document      => $document_obj,
    start_location => [$line, $column], # or just character position
    end_location  => [$line, $column], # or ppi-style location
    varname       => '$foo',
);

$tempvarmaker->schedule();
```

DESCRIPTION

Given a region of code within a statement, replaces that code with a temporary variable. Declares and initializes the temporary variable right above the statement that included the selected expression.

Usually, you simply set `start_position` to what `$editor->GetSelectionStart()` returns and `end_position` to `$editor->GetSelectionEnd() - 1`.

SEE ALSO

This class inherits from `Padre::Task::PPI`.

AUTHOR

Steffen Mueller `smueller AT cpan DOT org`

COPYRIGHT AND LICENSE

Copyright 2008–2010 The Padre development team as listed in `Padre.pm`.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl 5 itself.

