

**NAME**

`exp2`, `exp2f`, `exp2l` – base-2 exponential function

**SYNOPSIS**

```
#include <math.h>
```

```
double exp2(double x);
```

```
float exp2f(float x);
```

```
long double exp2l(long double x);
```

Link with `-lm`.

Feature Test Macro Requirements for glibc (see **feature\_test\_macros(7)**):

```
exp2(), exp2f(), exp2l():
```

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

**DESCRIPTION**

These functions return the value of 2 raised to the power of *x*.

**RETURN VALUE**

On success, these functions return the base-2 exponential value of *x*.

For various special cases, including the handling of infinity and NaN, as well as overflows and underflows, see **exp(3)**.

**ERRORS**

See **math\_error(7)** for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see **exp(3)**.

**VERSIONS**

These functions first appeared in glibc in version 2.1.

**ATTRIBUTES**

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
<b>exp2()</b> , <b>exp2f()</b> , <b>exp2l()</b>	Thread safety	MT-Safe

**CONFORMING TO**

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning *double* also conforms to SVr4, 4.3BSD, C89.

**SEE ALSO**

**cbrt(3)**, **cexp2(3)**, **exp(3)**, **exp10(3)**, **sqrt(3)**

**COLOPHON**

This page is part of release 4.09 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

