NAME

MooseX::Declare::Syntax::InnerSyntaxHandling − Keywords inside blocks

DESCRIPTION

This role allows you to setup keyword handlers that are only available inside blocks or other scoping environments.

METHODS

default_inner

```
ArrayRef[Object] Object->default_inner ()
```

Returns an empty `ArrayRef` by default. If you want to setup additional keywords you will have to `around` this method.

setup_inner_for

```
Object->setup_inner_for(ClassName $class, %args)
```

Sets up all handlers in the inner class.

REQUIRED METHODS

get_identifier

```
Str get_identifier ()
```

Required to return the name of the identifier of the current handler.

MODIFIED METHODS

setup_for

```
Object->setup_for(ClassName $class, %args)
```

After the keyword is setup inside itself, this will call ‘‘setup_inner_for’’.

SEE ALSO

- MooseX::Declare
- MooseX::Declare::Syntax::NamespaceHandling
- MooseX::Declare::Syntax::MooseSetup

AUTHORS

- Florian Ragwitz <rafl AT debian DOT org>
- Ash Berlin <ash AT cpan DOT org>
- Chas. J. Owens IV <chas DOT owens AT gmail DOT com>
- Chris Prather <chris AT prather DOT org>
- Dave Rolsky <autarch AT urth DOT org>
- Devin Austin <dhoss AT cpan DOT org>
- Hans Dieter Pearcey <hdp AT cpan DOT org>
- Justin Hunter <justin DOT d DOT hunter AT gmail DOT com>
- Matt Kraai <kraai AT ftbfs DOT org>
- Michele Beltrame <arthas AT cpan DOT org>
- Nelo Onyiah <nelo DOT onyiah AT gmail DOT com>
- nperez <nperez AT cpan DOT org>
- Piers Cawley <pdcawley AT bofh DOT org DOT uk>
- Rafael Kitover <rkitover AT io DOT com>
- Robert ’phaylon’ Sedlacek <rs AT 474 DOT at>
- Stevan Little <stevan DOT little AT iinteractive DOT com>
- Tomas Doran <bobtfish AT bobtfish DOT net>
- Yanick Champoux <yanick AT babyl DOT dyndns DOT org>



COPYRIGHT AND LICENSE

This software is copyright (c) 2011 by Florian Ragwitz.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.