

NAME

mtext_put_prop_values – Set multiple text properties with the same key.

SYNOPSIS

```
int mtext_put_prop_values (MTText * mt, int from, int to, MSymbol key, void ** values, int num)
```

DESCRIPTION

Set multiple text properties with the same key. The **mtext_put_prop_values()** function sets a text property to the characters between **from** (inclusive) and **to** (exclusive) in M-text **mt**. **key** and **values** specify the key and the values of the text property. **num** specifies the number of property values to be set.

RETURN VALUE

If the operation was successful, **mtext_put_prop_values()** returns 0. Otherwise it returns -1 and assigns an error code to the external variable **merror_code**.

ERRORS

MERROR_RANGE, MERROR_SYMBOL

SEE ALSO

mtext_put_prop(), **mtext_get_prop()**, **mtext_get_prop_values()**, **mtext_push_prop()**,
mtext_pop_prop(), **mtext_prop_range()**

COPYRIGHT

Copyright (C) 2001 Information–technology Promotion Agency (IPA)

Copyright (C) 2001–2011 National Institute of Advanced Industrial Science and Technology (AIST)

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License <<http://www.gnu.org/licenses/fdl.html>>.

