

MooseX::Declare::Syntax::Keyword::With(3pm) - contributed Perl Documentation
 MooseX::Declare::Syntax::Keyword::With(3pm)

NAME

MooseX::Declare::Syntax::Keyword::With – Apply roles within a class– or role–body

VERSION

version 0.43

SYNOPSIS

```
use MooseX::Declare;

class ::Baz {
    with 'Qux';
    ...
}
```

DESCRIPTION

The `with` keyword allows you to apply roles to the local class or role. It differs from the `with`–option of the `class` and `role` keywords in that it applies the roles immediately instead of deferring application until the end of the class– or role–definition.

It also differs slightly from the `with` provided by Moose in that it expands relative role names (`:::Foo`) according to the current namespace.

METHODS

parse

```
Object->parse(Object $context)
```

Will skip the declarator and make `with` invocation apply the set of specified roles after possible namespace–expanding has been done.

CONSUMES

- MooseX::Declare::Syntax::KeywordHandling

SEE ALSO

- MooseX::Declare
- MooseX::Declare::Syntax::Keyword::Namespace

AUTHOR

Florian Ragwitz <rafl AT debian DOT org>

COPYRIGHT AND LICENSE

This software is copyright (c) 2008 by Florian Ragwitz.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

