

MooseX::Getopt::Meta::Attribute(3pm) User Contributed Perl Documentation MooseX::Getopt::Meta::Attribute(3pm)

## NAME

MooseX::Getopt::Meta::Attribute – Optional meta attribute for custom option names

## VERSION

version 0.71

## SYNOPSIS

```
package App;
use Moose;

with 'MooseX::Getopt';

has 'data' => (
    metaclass => 'Getopt',
    is        => 'ro',
    isa       => 'Str',
    default   => 'file.dat',

    # tells MooseX::Getopt to use --somedata as the
    # command line flag instead of the normal
    # autogenerated one (--data)
    cmd_flag  => 'somedata',

    # tells MooseX::Getopt to also allow --moosedata,
    # -m, and -d as aliases for this same option on
    # the commandline.
    cmd_aliases => [qw/ moosedata m d /],

    # Or, you can use a plain scalar for a single alias:
    cmd_aliases => 'm',
);
```

## DESCRIPTION

This is a custom attribute metaclass which can be used to specify a the specific command line flag to use instead of the default one which MooseX::Getopt will create for you.

This is certainly not the prettiest way to go about this, but for now it works for those who might need such a feature.

### Use 'traits' instead of 'metaclass'

You should rarely need to explicitly set the attribute metaclass. It is much preferred to simply provide a trait (a role applied to the attribute metaclass), which allows other code to further modify the attribute by applying additional roles.

Therefore, you should first try to do this:

```
has 'foo' => (traits => ['Getopt'], cmd_flag => 'f');
```

### Custom Metaclass alias

This now takes advantage of the Moose 0.19 feature to support custom attribute metaclass aliases. This means you can also use this as the **Getopt** alias, like so:

```
has 'foo' => (metaclass => 'Getopt', cmd_flag => 'f');
```

## METHODS

### cmd\_flag

Changes the command-line flag to be this value, instead of the default, which is the same as the attribute name.

### cmd\_aliases

Adds more aliases for this command-line flag, useful for short options and such.

### has\_cmd\_flag

### has\_cmd\_aliases



MooseX::Getopt::Meta::Attribute(3pm) User Contributed Perl Documentation MooseX::Getopt::Meta::Attribute(3pm)

## SUPPORT

Bugs may be submitted through the RT bug tracker <https://rt.cpan.org/Public/Dist/Display.html?Name=MooseX-Getopt> (or `bug-MooseX-Getopt AT rt DOT cpan DOT org` [<mailto:bug-MooseX-Getopt AT rt DOT cpan DOT org>](mailto:bug-MooseX-Getopt AT rt DOT cpan DOT org)).

There is also a mailing list available for users of this distribution, at [<http://lists.perl.org/list/moose.html>](http://lists.perl.org/list/moose.html).

There is also an irc channel available for users of this distribution, at `#moose` on `irc.perl.org` [<irc://irc.perl.org/#moose>](irc://irc.perl.org/#moose).

## AUTHOR

Stevan Little [<stevan AT iinteractive DOT com>](mailto:stevan AT iinteractive DOT com)

## COPYRIGHT AND LICENSE

This software is copyright (c) 2007 by Infinity Interactive, Inc.

This is free software; you can redistribute it and/or modify it under the same terms as the Perl 5 programming language system itself.

