

NAME

SLSETI - Provides a new integer value for an internal parameter of Scrolled_title of type INTEGER or REAL. See the scrolled_title_params man page for a complete list of all the Scrolled_title internal parameters.

SYNOPSIS

```
CALL SLSETI (PNAM, IVAL)
```

C-BINDING SYNOPSIS

```
#include <ncarg/ncargC.h>
```

```
void c_slseti (char *pnam, int ival)
```

DESCRIPTION

PNAM	(an input constant or variable of type CHARACTER) specifies the name of the parameter to be set. Only the first three characters of the string are examined.
IVAL	(an input expression of type INTEGER) is the desired value of the internal parameter. If the internal parameter is of type INTEGER, it will be given the value IVAL. If the internal parameter is of type REAL, it will be given the value REAL(IVAL).

C-BINDING DESCRIPTION

The C-binding argument descriptions are the same as the FORTRAN argument descriptions.

USAGE

This routine allows you to set the current value of Scrolled_title parameters. For a complete list of parameters available in this utility, see the scrolled_title_params man page.

ACCESS

To use SLSETI or c_slseti, load the NCAR Graphics libraries ncarg, ncarg_gks, ncarg_c, and ncarg_c, preferably in that order.

MESSAGES

See the scrolled_title man page for a description of all Scrolled_title error messages and/or informational messages.

SEE ALSO

Online: ftitle, scrolled_title, scrolled_title_params, slgeti, slgetr, slogap, slrset, slsetr, stitle, ncarg_cbind.

Hardcopy: NCAR Graphics Fundamentals, UNIX Version; User's Guide for NCAR GKS-0A Graphics

COPYRIGHT

Copyright (C) 1987-2009

University Corporation for Atmospheric Research

The use of this Software is governed by a License Agreement.

